
STEEL ATTACHMENT



	NO. OF ANCHORAGE BOLTS REQUIRED		
CURB	LONG SIDE	SHORT SIDE	
LXS	2 @ 34.5" O.C.	2 @ 19" O.C.	
LXL	2 @ 34.5" O.C.	2 @ 29" O.C.	
SUN3672	2 @ 60.5" O.C.	2 @ 24.75" O.C.	
PRD3715	2 @ 68.88" O.C.	2 @ 39" O.C.	
PRS	2 @ 58.88" O.C.	2 @ 28.69" O.C.	
PRL	2 @ 72" O.C.	2 @ 41.5" O.C.	
SAV1518	3 @ 54.56" O.C	2 @ 68.13" O.C.	
SAV2025	3 @ 61.56" O.C	2 @ 68.13" O.C.	
SAV28	3 @ 69.75" O.C	2 @ 68.13" O.C.	


ASSUMES:

CONC SLAB f'c= 4000PSI MINIMUM 4" MIN THICKNESS NORMAL WEIGHT CONCRETE MIN. 7-1/4" EDGE DISTANCE

Meets seismic requirements for the following codes: CBC 2022 IBC 2021

ROOF ANCHORAGE DETAIL		
CBKD Series	CBWC Series	
LXS	LXS	
LXL	LXL	
SUN3672	SUN3672	
PRD3715	PRD3715	
PRS	PRS	
PRL	PRL	
SAV1518	SAV1518	
SAV2025	SAV2025	
SAV28	SAV28	

CONCRETE ATTACHMENT




CENTER ON CURB FLANGE. SEE TABLE FOR QUANTITY OF EVENLY SPACED 1/2" Ø THREADED ROD IN HILTI HIT-HY 200 V3 EPOXY WITH 2-1/2" **EMBED**

	NO. OF ANCHORAGE BOLTS REQUIRED		
CURB	LONG SIDE	SHORT SIDE	
LXS	2 @ 34.5" O.C.	2 @ 19.0" O.C.	
LXL	2 @ 34.5" O.C.	2 @ 29" O.C.	
SUN3672	2 @ 60.5" O.C.	2 @ 24.75" O.C.	
PRD3715	4 @ 22.96" O.C.	2 @ 39" O.C.	
PRS	2 @ 58.88" O.C.	2 @ 28.69" O.C.	
PRL	3 @ 36" O.C.	2 @ 41.5" O.C.	
SAV1518	4 @ 36.38" O.C.	2 @ 68.13" O.C.	
SAV2025	4 @ 41.04" O.C.	3 @ 34.06" O.C.	
SAV28	5 @ 34.88" O.C.	3 @ 34.06" O.C.	

* SIX INCHES FROM EACH CORNER EVENLY SPACED. ** CENTERED.

WOOD ATTACHMENT



CENTER ON CURB FLANGE. SEE TABLE FOR QUANTITY OF EVENLY SPACED

1/4" Ø x 3.5" SIMPSON SDS SCREWS W/2.25" THREADED EMBED INTO WOOD FRAMING

FOUR	INCHES	FROM	EACH
CORN	IFR FVF	NI Y SE	ACFD





3847 WABASH DRIVE MIRA LOMA, CA 91725

PHONE (951) 685-1101 FAX (619) 872-9799

	REQUIRED		
CURB	LONG SIDE	SHORT SIDE	
LXS	4 @ 12.83" O.C.	3 @ 11.5" O.C.	
LXL	4 @ 12.83" O.C.	3 @ 16.5" O.C.	
SUN3672	4 @ 21.5" O.C.	3 @ 14.38" O.C.	
PRD3715	7 @ 12.15" O.C.	5 @ 10.75" O.C.	
PRS	4 @ 20.96" O.C.	3 @ 16.35" O.C.	
PRL	6 @ 15.2" O.C.	4 @ 15.17" O.C.	
SAV1518	6 @ 22.63" O.C.	5 @ 18.03" O.C.	
SAV2025	7 @ 21.19" O.C.	5 @ 18.03" O.C.	
SAV28	8 @ 20.5" O.C.	5 @ 18.03" O.C.	

NO. OF ANCHORAGE SCREWS



SUBMITTED TO: COMPANY: JOB NAME:	FORM NO: CB-60			
EQUIPMENT:	DATE:	REV:	DRAWN BY:	
NOTES:	8/28/2023	10	FMM	