FEATURES

- Direct coupled style actuator standard.
- CA Title 24 Compliant
- Stainless steel damper side seals.
- AMCA certified CD-60 Airfoil dampers blades.
- Meets leakage rate as required by ASHRAE 90.1.
- · External linkage system.
- · Mechanically secured outside air intake filter.
- Capable of introducing up to 100% outdoor air.
- Metal Filter 19"x 16- 1/16"x 7/8" (exact) included.

FEATURES (When Ordered With Control Options)


- · Controls are FDD Compliant.
- Fully modulating damper controls with enthalpy, dry bulb and differential temperature sensor options.
- Selectable economizer changeover temperature set point.
- Requires part number 6210-0010J for Dual Enthalpy.
- CO2 controller standard.

Wall or duct mounted CO2 sensor provided as option:

CO2WM - Wall Mount CO2DM - Duct Mount

LEED ECONOMIZER OPTION

- ProVent P/N: FLOWECAFF1860
- Outside air measurement for dilution utilizing thermal dispersion technology and ASHRAE 62.1 compliant. Provides LEED credit by supplying feedback on ventilition system performance ensuring that the ventilation system maintains design requirements.
- Factory installed onto economizer standard.
- Provides analog outputs for BMS, visual or audible alert, and generates an alarm when conditions vary by 10% or more of set point.



VERTICAL ECONOMIZER FOR YORK UNITS

DNQ/DNY/DNZ/DEQ/DEZ/BHQ/BHX/BHZ 024-060 DNX/DEX 024-060, DEY 060

30"

ProVent P/N Wt.

ECODAFF1860AC1
(Actuator Only, 2-10 VDC)

ECODAFF1860DB1
(Fully Modulating Dry Bulb)


ECODAFF1860EN1

50 Lb.



(Fully Modulating Enthalpy)

Note: For factory installed LEED economizer option, part number FLOWECAFF1860 must be added.



3847 WABASH DRIVE

PHONE (951) 685-1101 FAX (619) 872-9799

MIRA LOMA, CA 91752

SUBMITED TO:	FORM NO:	PART NUMBER:	
COMPANY:	ECO-215	ECODAFF1860 Series	
JOB NAME:	DATE:	REV:	DRAWN BY:
EQUIPMENT:	2/26/2016	11	CNG
NOTES:	2,20,2010	• •	0.10

