

FEATURES <ul style="list-style-type: none">• Painted hood and panel matches factory specifications and color.• Designed for unit mounted down or horizontal discharge. (End horizontal return requires duct mounted.)• Includes gravity backdraft damper with fixed position option.• Insulated panel.• Includes water entrainment filter: 9-1/2" x 9-1/4" x 7/8" - 3761 12-5/8" x 12-5/8" x 7/8" - 7815• Upper panel is used for both models.	0-25% OUTSIDE AIR HOOD WITH METAL FILTER FOR YORK UNITS		ProVent P/N:		Weight	
	ZT, ZH, ZJ, ZR, KT, KJ 037-150 ZF, XP, ZB, WP, KB 078-150		OAPRD376125FBC (3 to 5 Tons)		28 Lbs	
			OAPRD781525FBC (6½ to 12½ Tons)		28 Lbs.	
<p>Upper Panel</p> <p>31 7/8"</p> <p>24 11/16"</p>						
	3847 WABASH DRIVE MIRA LOMA, CA 91752 PHONE (951) 685-1101 FAX (619) 872-9799		SUBMITTED TO: _____ COMPANY: _____ JOB NAME: _____ EQUIPMENT: _____ NOTES: _____		FORM NO: OA-11	
					DATE: 2/10/2025	REV: 2