



FEATURES

- Roof curb perimeter made of galvanized steel.
- Gasketing package provided.
- Heat treated wood nailer provided.
- Corner flanges are pre-threaded for easy bolt on assembly.
- Pitched, adjustable pitch/ adjustable height, welded, different height, isolation and calculated curbs are available.

NOTES

- Attach ductwork to roof curb. Flanges of duct rest on top of curb. Support ductwork below the curb.

KNOCK-DOWN ROOF CURBS FOR YORK UNITS

ZJ/ ZR 180-300; ZF 210-300; XP 180-240

General Table

PROVENT P/N	A	EST. WEIGHT
CBKDLSLM183008	8"	174 Lbs.
CBKDLSLM183011	11"	188 Lbs.
CBKDLSLM183014	14"	237 Lbs.

SEISMIC KIT P/N

KDKITSLM1830

Meets seismic requirements for the following codes:
CBC 2019
IBC 2018



3847 WABASH DR.
MIRA LOMA, CA 91725

PHONE (951) 685-1101
FAX (619) 872-9799

SUBMITTED TO: _____
COMPANY: _____
JOB NAME: _____
EQUIPMENT: _____
NOTES: _____

FORM NO:
CBKD-105

PART NUMBER:
CBKDLSLM1830 SERIES

DATE:
04/21/2021

REV:
M3

DRAWN BY:
CNG