

<u>FEATURES</u>	KNOCK-DOWN ROOF CURBS FOR SUNCHOICE UNITS	PROVENT P/N	A	EST. WEIGHT	SEISMIC KIT P/N
<ul style="list-style-type: none"> • Roof curb perimeter made of galvanized steel. • Gasketing package provided. • Heat treated wood nailer provided. • Corner flanges are pre-threaded for easy bolt on assembly. • Pitched, adjustable pitch/ adjustable height, welded, different height, isolation and calculated curbs are available. 	AV, AD20-25; AE13-15; AH, AL18-20	CBKDSAV202508**	08"	335 Lbs.	KDKITSAV2025 <div style="border: 1px solid black; width: 100%; height: 100%; text-align: center; line-height: 1.2;"> When conforming to CBC 2019 and IBC 2018, include optional seismic kit. Available for 8"- 18" </div>
		CBKDSAV202511**	11"	380 Lbs.	
		CBKDSAV202514**	14"	425 Lbs.	
		CBKDSAV202518**	18"	525 Lbs.	
		CBKDSAV202524**	24"	717 Lbs.	
<u>NOTES</u>					
<ul style="list-style-type: none"> • Attach ductwork to roof curb. Flanges of duct rest on top of curb. Support ductwork below the curb. • CBKDSAV202518 will be 12GA perimeter 					
<u>CORNER DETAIL</u>	**CBKDSAV202518 will be 12GA perimeter**			<u>CROSS SECTION DETAIL</u>	

	3847 WABASH DRIVE MIRA LOMA, CA 91752	SUBMITTED TO: _____ COMPANY: _____ JOB NAME: _____ EQUIPMENT: _____ NOTES: _____	FORM NO: -	PART NUMBER: CBKDSAV2025 SERIES
	PHONE (951) 685-1101 FAX (619) 872-9799	DATE: 3/14/2023	REV: 1	DRAWN BY: CNG